

Traffic H1

Horizontal barrier


MAGNETIC[®]
ACCESS TO PROGRESS



For demanding security tasks

As horizontal barriers, the Traffic H1 is a specialist in vehicle and pedestrian management. It is not only used for blocking access to tunnels and lanes. It exploits its full potential when controlling junctions where traffic alternates in longitudinal and transverse directions. It is therefore not only the optimal solution for road traffic, but also for protecting material flows in production plants.

With its patented folding boom, the Traffic H1 can therefore even block crossings where the ratio of lane widths in the longitudinal and transverse directions is greater than 2:1. At the heart of the Traffic H1 is the innovative MHTM™ drive, characterised by its energy efficiency, lack of maintenance, and long service life – the Traffic H1 is designed for 10 million opening and closing cycles.



Horizontal turning movements

As horizontal barriers, Traffic H1 can also be used in areas with limited heights. Swivel mode also allows alternate blocking of crossings in longitudinal and transverse directions.




Innovative drive technology

The MHTM™ drive unit operates without maintenance, energy-efficiently and quietly. Its high torque ensures best possible operation even under extreme weather conditions.



Legal security

Horizontal barriers from Magnetic have a conformity declaration in line with the Machinery Directive. So operators and installers are always on the safe side regarding liability issues.



Easy access to components

Two simple hand movements suffice: easy access to the control system and drive unit by removing the hood and front panel. This increases user-friendliness and speeds up commissioning and servicing.

Traffic H1

Horizontal barrier

- > High functionality for numerous special applications
- > Patented folding boom for safety at indoor crossings with differing lane widths
- > Low power consumption for economical operation
- > Optimum accessibility for particularly simple maintenance
- > Form based on the prizewinning design of the Access barriers




Technical Data	H1LE with standard boom	H1LE with folding boom	H1SE
Barrier width	max. 6.0 m	max. 4.5 m	max. 3.5 m
Opening/closing time	4.0 s	4.0 s	2.0 s
Power consumption	max. 45 W	max. 45 W	max. 90 W
Drive technology	MHTM™	MHTM™	MHTM™
Voltage	85–264 VAC, 50/60 Hz	85–264 VAC, 50/60 Hz	85–264 VAC, 50/60 Hz
Duty cycle	100 %	100 %	100 %
Housing dimensions (W x D x H) without support	315 x 360 x 940 mm	–	315 x 360 x 940 mm
Housing dimensions (W x D x H) with support	315 x 360 x 1355 mm	315 x 360 x 1355 mm	–
Enclosure rating	IP 54	IP 54	IP 54
Temperature range	–30 to +55 °C	–30 to +55 °C	–30 to +55 °C
Weight (without boom)	55 kg	55 kg	55 kg

Features	H1LE with standard boom	H1LE with folding boom	H1SE
Standard colours	RAL 2000	RAL 2000	RAL 2000
Barrier boom	MicroBoom-H1	MicroBoom-F1	MicroBoom-H1
Control system	MGC Pro	MGC Pro	MGC Pro
Integrated 2-channel detector for induction loops	Standard	Standard	Standard
Modular expansion of control system	Freely expandable	Freely expandable	Freely expandable
Variable I/O assignment	Standard	Standard	Standard
Number of digital inputs	8	8	8
Number of relay/digital outputs	6/4	6/4	6/4
Input for safety photoelectric switch with test	Standard	Standard	Standard
Selectable closing speed	Standard	Standard	Standard
Selectable opening speed	Standard	Standard	Standard


Options	H1LE	H1SE
Special colours	✓	✓
Grating	✓	
Folding boom	✓	
Hood lights	✓	✓
Key-operated switch	✓	✓
Radio module	✓	✓
Ethernet module	✓	✓
RS485 module	✓	✓
CAN module (counting)	✓	✓
Electronic end-position locking	✓	✓

Dimensional drawings



Access to Progress

Magnetic stands for pioneering products – in every way. Our access control systems for vehicles or pedestrians clear the way for thousands of people every day – at car parks, toll gates, stations, airports and in buildings. Our technology is also pioneering, however: with innovative drives, intelligent control systems and well thought-out details it provides maximum safety and longevity. Are you also on the path to Magnetic?



Vehicle barriers

Access barriers
Parking barriers
Toll barriers
Special barriers



Pedestrian gates

Turnstiles
Swing gates
Tripod gates
Retractable gates
Wing gates



Terminals

Cars
Trucks

Germany
MAGNETIC AUTOCONTROL GMBH
Grienmatt 20
79650 Schopfheim
Phone +49 7622 695-5
Fax +49 7622 695-800
E-mail info@magnetic-germany.com

Australia
MAGNETIC AUTOMATION PTY LTD
38 Metrolink Circuit
Campbellfield, VIC 3061
Phone +61 3 9339 2900
E-mail info@magnetic-oz.com

Brazil
MAGNETIC AUTOCONTROL LTDA
Av. Salim Antônio Curiati, 136
04690-050 – São Paulo
Phone +55 11 5660 8500
E-mail info@magnetic-br.com

China
MAGNETIC CONTROL SYSTEMS CO., LTD
No. 3 Building, No. 51
Lane 1159, Kang Qiao (East) Road
Kang Qiao Industrial Zone, Shanghai
Phone +86 21 68182970
E-mail info@magnetic-cn.com

France
FAAC FRANCE
377 Rue Ferdinand Perrier
69808 St Priest Cedex
Phone +33 4 72 21 86 89
E-mail info@magnetic-fr.com

India
MAGNETIC AUTOCONTROL PVT LTD.
PRS Centre
Plot No. 373 to 376, 2nd Floor (West Wing)
1st Cross Street, Nehru Nagar
Old Mahabalipuram Road
Kottivakkam (Opp Rayala Technopark, Perungudi)
Chennai 600041
Phone +91 44 421 23297
E-mail info@magnetic-india.com

Middle East
FAAC MIDDLE EAST FZE
Dubai Silicon Oasis
PO Box 54886
Dubai
United Arab Emirates
Phone +971 4 3724193
E-mail info@magnetic-uae.com

N. and S. America (excl. Brazil)
FAAC INTERNATIONAL, INC
3160 Murell Road
Rockledge, FL 32955
USA
Phone +1 321 635 8585
E-mail info@magnetic-usa.com

Scandinavia
FAAC NORDIC AB
Box 125
284 22 Perstorp
Sweden
Phone +46 435 77 95 03
E-mail info@magnetic-nordic.com

Southeast Asia
MAGNETIC CONTROL SYSTEMS SDN. BHD
No. 17, Jalan Anggerik Mokara 31/54
Taman Perindustrian Kota Kemuning
40460 Shah Alam
Selangor Darul Ehsan
Malaysia
Phone +60 3 5123 0033
E-mail info@magnetic-malaysia.com